

Flow switch for domestic applications 615 & 622

An Ideal flow switch for domestic showers and water pumps etc.

- Supplied complete with compression fittings
- SPDT (C/O) contacts
- User adjustable (factory set to minimum flow)
- 1m of 3-core cable

Model: 615 For 15mm copper pipe

Model: 622 For 22mm copper pipe



[See DataFax 2134P for Prices & Fitting Instructions](#)

All wetted parts are WRAS Approved

Suitable for use with water only. For use with other media contact PVL Ltd

Technical Data:	
Maximum operating pressure	8 bar static
Maximum operating temperature	Liquid 85 deg C
Minimum operating temperature	Liquid 5 deg C
Maximum ambient temperature	70 deg C
Minimum ambient temperature	5 deg C
Maximum flow rate	20 l/min
Maximum operating voltage	250 V
Current rating	16A Res (4A Ind)
Enclosure protection	IP54

PRESSURE-VACUUM-LEVEL LTD

Unit 9, Lexden Lodge Industrial Estate, Jarvis Brook,
Crowborough, East Sussex, TN6 2NQ U.K.

Tel: +44(0)1892 66 44 99 Fax: +44(0)1892 66 36 90

Web: www.pvl.co.uk Email: info@pvl.co.uk

