


Media: air – water – gas
 Pressure range: 1 to 50 bar max
 Media temperature: 130° C max
 Ambient temperature: -10° to +50° C max
 Media viscosity: 25 centistokes max
 Mounting: any position




NC

2/2 Brass

**N/CLOSED HIGH PRESSURE
 2 WAY SERVO ASSISTED**

TYPE E119



PRESSURE

Ø Port	Ø Orifice (mm)	Flow Rate Cv L/min	Pressure (bar)		Part Number	List Price
			Min ΔP	Max ΔP		
3/8 BSP	12	33	1	50	E119CW12/5 + voltage	£146.06
1/2 BSP	12	37	1	50	E119DW12/5 + voltage	£146.06

OPTIONS

Connector PG9 – DIN 43650 A	Included
-----------------------------	----------

ELECTRICAL DATA

voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 12-24-48-110-230 (50 or 60 Hz)	36	48 VA	26 VA	F 155°C	IP 65 with connector	3 spades DIN 43650A DIN 40050 VDE 0110
= 12-24-48		14 W				

CONSTRUCTION

Body: brass
 Tube and internal parts: stainless steel
 Seals and gaskets: PTFE
 Moulded coil: resin

REPAIR KIT

Coil	36 + voltage
Complete plunger + O' rings + membrane	KIT E119(C or D) W12/5

OVERALL DIMENSIONS

