



Media: air - water - light oil- vacuum
 Pressure range: 0 to 100 bar max
 Media temperature: 100° C max
 Ambient temperature: -10° to +50° C max
 Media viscosity: 40 centistokes max
 Mounting: Vertical position coil up
 Weight (including coil): 500 g
 Opening or closing time: 20 m/sec max



2/2 Brass

**N/OPEN
 2 WAY DIRECT ACTING
 TYPE WFH**



PRESSURE

Ø Port	Ø seat (mm)	Kv L/mn	Min ΔP	Pressure (bar)	seals	Fluid temp. Max °C	Part Number	List Price
1/8 or 1/4 BSP	0.6	0.20	0	200	NBR FKM	100°C	WF0.6 H NBR + port + voltage WF0.6 H FKM + port + voltage	£132.62
	0.8	0.30	0	130	NBR FKM	100°C	WF0.8 H NBR + port + voltage WF0.8 H FKM + port + voltage	
	0.9	0.40	0	100	NBR FKM	100°C	WF0.9 H NBR + port + voltage WF0.9 H FKM + port + voltage	
	1	0.50	0	70	NBR FKM EPDM	100°C	WF1H NBR + port + voltage WF1H FKM + port + voltage WF1H EPDM + port + voltage	
	1.2	0.67	0	50	NBR FKM EPDM	100°C	WF1.2H NBR + port + voltage WF1.2H FKM + port + voltage WF1.2H EPDM + port + voltage	
	1.5	0.95	0	35	NBR FKM EPDM	100°C	WF1.5H NBR + port + voltage WF1.5H FKM + port + voltage WF1.5H EPDM + port + voltage	
	2	1.60	0	20	NBR FKM EPDM	100°C	WF2H NBR + port + voltage WF2H FKM + port + voltage WF2H EPDM + port + voltage	
	2.2	1.80	0	15	NBR FKM EPDM	100°C	WF2.2H NBR + port + voltage WF2.2H FKM + port + voltage WF2.2H EPDM + port + voltage	
2.5	2.30	0	12	NBR FKM EPDM	100°C	WF2.5H NBR + port + voltage WF2.5H FKM + port + voltage WF2.5H EPDM + port + voltage		

OPTIONS

Connector DIN 43650 A NPT thread Seals and gaskets in PTFE Explosion Proof Enclosure ATEX II 2 G/D Eex d IIC T6, IP65 85°C (Ambient T° from -20°C to +40°C)	Included +£23.68 +£22.55 +£199.33
--	---

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24-48-110-230 (50 / 60 Hz)	40	48 VA	24 VA	F 155°C	IP 65 with connector	3 spades DIN 43650 DIN 40050 VDE 0110
= 12-24-48		14 W - 20 W				

CONSTRUCTION

Body, tube and internal parts: stainless steel
 Seals and gaskets: NBR-FKM-EPDM
 Moulded coil: resin

REPAIR KIT

Coil	40 + voltage
Complete plunger	KIT + valve part number

OVERALL DIMENSIONS

