

**Pressure switch with scale****B12..****FEATURES**

- -0.2 to 300 bar adjustment ranges
- Adjustable differential
- Overpressure upto 350 bar
- C/O contacts
- Switch rating 415Vac/6A(Ind)
- 1/4"BSP standard thread
- Pressure & Hysteresis adjustment scales
- Stainless steel or brass wetted parts



B12FN Illustrated

TYPE	RANGE bar	DIFFERENTIAL bar	MAXIMUM PRESSURE	MAXIMUM FLUID TEMP	MAXIMUM BODY TEMP
B12CN	-0.2 to 8	0.6 to 3	9 bar	120degC	- 35 to + 60degC
B12DN	5 to 16	1 to 3.5	18 bar		
B12EN	8 to 28	2 to 6	29 bar		
B12FN	12 to 50	6 to 15	60 bar	80degC	- 35 to + 60degC
B12GN	25 to 150	12 to 40	180 bar		
B12HN	60 to 300	40 to 80	350 bar		

Maximum voltage	415Vac	Thread - B12C/D/E	1/4"BSP Female
Microswitch rating	16A res (6A ind)	Thread - B12F/G/H	1/4" BSP Male
Electrical contacts	SPDT (C/O)	Protection	IP 40

**PRESSURE-VACUUM-LEVEL LTD**

Unit 9, Lexden Lodge Industrial Estate, Jarvis Brook,  
Crowborough, East Sussex, TN6 2NQ U.K.

Tel: +44(0)1892 66 44 99 Fax: +44(0)1892 66 36 90

Web: [www.pvl.co.uk](http://www.pvl.co.uk) Email: [info@pvl.co.uk](mailto:info@pvl.co.uk)

