

Level Switch - remote mounting**RMFS****FEATURES**

- Aluminium housing
- Nitrile or stainless steel float
- 1/4" BSP inlet & outlet ports
- Screwed end caps with o-ring
- Integral mounting flange

An external fluid-level float switch, the IP68 rated RMFS is fixed vertically either direct to the vessel wall or to a secondary bracket via an integral mounting flange.



Technical data	
Body material	Aluminium
Stem material (float switch)	Stainless steel
Float material	Buna-N or Stainless steel
Max. switching capacity	50VA
Max. switching voltage	Upto 300V ac/dc
Max. switching current	0.5A
Max. switching resistance	100m OHMS
Temperature range	-10°C to +100°C
Max. operating pressure	10 Bar (Buna-N)
Max. operating pressure	30 Bar (S/steel)
Switch position	N/O or N/C (reversible)
Float switch specific gravity	Buna-N = 0.47 S/steel = 0.75

PRESSURE-VACUUM-LEVEL LTD

Unit 9, Lexden Lodge Industrial Estate, Jarvis Brook,
Crowborough, East Sussex, TN6 2NQ U.K.

Tel: +44(0)1892 66 44 99 Fax: +44(0)1892 66 36 90

Web: www.pvl.co.uk Email: info@pvl.co.uk

