


Media: air – water – gas – light oil - vacuum
 Pressure range: 0 to 25 bar max
 Media temperature: 100° C max
 Ambient temperature: -10° to +50° C max
 Media viscosity: 40 centistokes max
 Mounting: any position
 Weight (including coil): 150g
 Opening Closing time: 15 mSec Max

2/2 Brass

N/CLOSED or N/OPEN
 2 WAY DIRECT ACTING

TYPE 200200



PRESSURE

TYPE	Ø Port	Ø Orifice (mm)	Flow Rate Ltr/min	Pressure (bar)			Part Number	List Price
				Min ΔP	Max ΔP			
					AC	DC		
2/2 NC	1/8 BSP	1.2	0.65	0	25	25	212200 + seal + 0181 + voltage	£25.41
		1.5	1	0	20	16	215200 + seal + 0181 + voltage	
		2	1.5	0	15	10	220200 + seal + 0181 + voltage	
		2.5	2.3	0	7	4.5	225200 + seal + 0181 + voltage	
		3.1	3.1	0	4	1.8	231200 + seal + 0181 + voltage	
2/2 NO	1/8 BSP	1.2	0.65	0	16	16	212200 + seal + 0180 + voltage	£33.80
		1.5	1	0	11.5	11.5	215200 + seal + 0180 + voltage	
		2	1.4	0	5	5	220200 + seal + 0180 + voltage	
		2.5	2.1	0	3.5	3.5	225200 + seal + 0180 + voltage	
		3.1	2.8	0	2.5	2.5	231200 + seal + 0180 + voltage	

OPTIONS

Connector PG9 – DIN 43650 B IP65Coil NPT Thread Manual Over Ride ¼ BSP	Included Included +£23.68 +£6.62 +5%
--	--

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 48 - 110 - 230 (50 or 60 Hz)	22	14 VA	9 VA	F 155°C	IP 65 with connector	3 spades DIN 43650B DIN 40050 VDE 0110
= 12 - 24 - 48		6 Watts				

CONSTRUCTION

Body: Brass
 Tube and internal parts: Stainless steel
 Seals and gaskets: NBR or EPDM or FKM
 Moulded coil: Resin

REPAIR KIT

Coil	22 + voltage
Complete plunger + O' rings	KIT + valve part number

OVERALL DIMENSIONS

