


Media: air – water – gas – light oil - vacuum
 Pressure range: 0 to 30 bar max
 Media temperature: 100° C max
 Ambient temperature: -10° to +50° C max
 Media viscosity: 40 centistokes max
 Mounting: any position
 Weight (including coil): 300 g
 Opening Closing time: 20 mSec Max

2/2 Brass

N/CLOSED or N/OPEN
 2 WAY DIRECT ACTING

TYPE 200201



PRESSURE

TYPE	Ø Port	Ø Orifice (mm)	Flow Rate Cv L/min	Pressure Rating (bar) Max ΔP			Part Number	List Price	
				Min ΔP	AC 10w Coil	DC 10w Coil			DC 18w Coil
2/2 NC	1/8 BSP	1.5	1.2	0	30	26	30	215201 + seal + 0181 + voltage	£35.99
		2	1.7	0	22	20	30	220201 + seal + 0181 + voltage	
		2.5	2.5	0	16	14	25	225201 + seal + 0181 + voltage	
		3.5	5.4	0	10	7.5	20	235201 + seal + 0181 + voltage	
	1/4 BSP	1.5	1.2	0	30	26	30	215201 + seal + 0141 + voltage	
		2	1.7	0	22	20	30	220201 + seal + 0141 + voltage	
		2.5	2.5	0	16	14	25	225201 + seal + 0141 + voltage	
		3.5	5.4	0	10	7.5	20	235201 + seal + 0141 + voltage	
	3/8 BSP	4.5	6.9	0	6	3.5	7	245201 + seal + 0141 + voltage	
		5.2	7.9	0	4	1.8	5	252201 + seal + 0141 + voltage	
		5.2	7.9	0	4	1.8	5	252201 + seal + 0381 + voltage	
		6	10.5	0	2.4	0.4	-	260201 + seal + 0381 + voltage	
2/2 NO	1/8 BSP	7.5	15	0	1.5	0.25	-	275201 + seal + 0381 + voltage	£50.54
		1.5	0.65	0	20	-	20	215201 + seal + 0180 + voltage	
		2	1	0	16	-	16	220201 + seal + 0180 + voltage	
		2.5	1.4	0	12	-	12	225201 + seal + 0180 + voltage	
	1/4 BSP	3.5	2.1	0	5	-	5	235201 + seal + 0180 + voltage	
		1.5	1.2	0	20	-	20	215201 + seal + 0140 + voltage	
		2	1.5	0	16	-	16	220201 + seal + 0140 + voltage	
		2.5	2.2	0	12	-	12	225201 + seal + 0140 + voltage	
		3.5	4.9	0	5	-	5	235201 + seal + 0140 + voltage	
		4.5	6.2	0	3	-	3	245201 + seal + 0140 + voltage	
		5.2	7.9	0	1.5	-	1.5	252201 + seal + 0140 + voltage	

OPTIONS

Connector PG9 – DIN 43650 A
 Explosion Proof Enclosure ATEX II 2 G/D EexdIICt6, IP65 85°C (Ambient T° from -20°C to +40°C) (N/Closed only)
 Manual Over Ride
 High power 18 – 20 watt coil (higher DC pressure ratings)
 NPT Thread



Included
 +£199.33
 +£7.20
 +£5.27
 +£23.68

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 48 - 110 - 230 (50 or 60 Hz)	30	26 VA	14 VA	F 155°C	IP 65 with connector	3 spades DIN 43650A DIN 40050 VDE 0110
= 12 - 24 - 48 - 80 - 190 (DC)	30	10 Watts				
	36	14 - 20 Watts				

CONSTRUCTION

Body: Brass
 Tube and internal parts: 304 stainless steel, armature 430F stainless steel
 Seals and gaskets: NBR (Optional EPDM or FKM)
 Moulded coil: Resin

REPAIR KIT

Coil	Coil size (30 or 36) + voltage
Complete plunger + O rings	KIT + valve part number

OVERALL DIMENSIONS

