

Media: air – water – gas – light oil
 Pressure range: 2 to 10 bar max
 Media temperature: 60° C max
 Ambient temperature: -10° to +60° C max
 Media viscosity: 40 centistokes max
 Mounting: any position
 Weight (including coil): 365g
 Opening / Closing Time: 50 mSec



3/2 Aluminium

N/CLOSED & N/OPEN
 3 WAY SERVO ASSISTED

TYPE PU315/310



PRESSURE

	Ø Port	Ø Orifice (mm)	Flow Rate	Pressure Rating (bar)			Seals	Max Media Temp °C	Part Number	List Price
			Cv Ltr/ min	Min ΔP	Max ΔP	Max Working				
N/C	3/8 BSP	3.9	5.8	2	7	10	NBR	60	PU31503A + voltage	£43.05
N/O	3/8 BSP	3.9	5.8	2	7	10	NBR	60	PU31003A + voltage	

OPTIONS

Connector PG9 – DIN 43650 A IP65 Coil NPT Thread Explosion Proof Coil: EExmIIT4 ATEX II G IP65 T 130°C 	Included +10% +£53.08
---	-----------------------------

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 110 - 220 (50 or 60 Hz)	22001	11.6VA	8.5VA	F 155°C	IP 65 with connector	3 spades DIN 43650B DIN 40050 VDE 0110
= 12 - 24 - 48		4.5 Watts				

CONSTRUCTION

Body: Anodised Aluminium
 Tube and internal parts: Stainless steel
 Seals and gaskets: NBR
 Moulded coil: Resin

REPAIR KIT

Coil	22001 + voltage
Complete plunger + O' rings	22001 + seal material

OVERALL DIMENSIONS

