



Media: air - water - light oil- vacuum
 Pressure range: 0 to 25 bar max
 Media temperature: 100° C max
 Ambient temperature: -10° to +50° C max
 Media viscosity: 40 centistokes max
 Mounting: Vertical position coil up
 Weight (including coil): 500 g
 Opening or closing time: 20 m/sec max



3/2 Brass + St St N/Closed High Pressure 3 WAYS DIRECT OPERATED



TYPE RH

PRESSURE

Ø Port	Ø seat (mm)		Body Material	Min ΔP	Max ΔP (bar)	Part Number	List Price
	1→2	2 3					
1/8 or 1/4 BSP	1.0	1.2	Brass	0	25	R1 - 1.2 + port + seal + voltage	£115.78
			Brass	0	25	R1 - 1.7 + port + seal + voltage	
			Brass	0	25	R1 - 2.2 + port + seal + voltage	
1/8 or 1/4 BSP	1.0	1.2	Stainless	0	25	R1H - 1.2 + port + seal + voltage	£210.35
			Stainless	0	25	R1H - 1.7 + port + seal + voltage	
			Stainless	0	25	R1H - 2.2 + port + seal + voltage	

OPTIONS

Connector DIN 43650 A NPT thread Seals and gaskets in PTFE Explosion proof enclosure: protection II 2 G/D EExdIICT6 according to ATEX	Included +£22.55 +£22.55 +£199.33
------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------

ELECTRICAL DATA

voltage (-10% + 15%) Continuous duty 100%	Coil Size	Power		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24-48-110-230 (50 / 60 Hz)	40	48 VA	24 VA	F 155°C	IP 65 with connector	3 spades DIN 43650 DIN 40050 VDE 0110
= 12-24-48		14 W - 20 W				

CONSTRUCTION

Stainless steel version: Body, tube and internal parts: stainless steel
 Brass version: Body Brass, tube and internal parts stainless steel
 Seals and gaskets: NBR-FKM-EPDM
 Moulded coil: resin

REPAIR KIT

Coil	40 + voltage
Complete plunger	KIT + valve part number

OVERALL DIMENSIONS

